

## Vended Stack Dryer

At Huebsch®, our priority is making commercial laundry equipment that's perfectly aligned with your business philosophy. In other words, because you believe that profit is the inevitable result of superior efficiency, durability, simplicity and service, that's exactly what we deliver.

### FAST DRYING TIMES

Huebsch dryers offer a 7.0 cu. ft. cylinder with an 18 lb capacity offers ample space for large loads to tumble and product fast drying times, while lowering utility consumption.

### SOLID BASE

Huebsch dryers are built on sturdy steel bases to ensure years of worry-free performance.

### SPACE SAVINGS

A stack dryer gives your vended laundry all the benefits of two stand-alone dryers in a space of one machine. The stack utilizes all the same connections as a standard dryer, so there are no special hookups required.

### UNMATCHED DURABILITY

Built with premium materials and tested to meet the demands of the harshest environments, these commercial-grade machines deliver reliable, efficient operation load after load—and they're backed up by Huebsch's standard three-year warranty.\*

\*Parts only, labor not included. See Huebsch Warranty Bond for specifics.



### MICRO-DISPLAY CONTROL II

The Micro-Display Control II features a time-remaining countdown, coin countdown and cycle status lights.

- Capacitive Touch buttons are durable, inside and out, and reliable for years of use without looking worn
- White LED lights on buttons
- Integrated Wifi
- NFC allows programming using your phone/tablet, Android only

## Vended **Stack Dryer** specifications

### Specifications

Control Options		MDC II
Models	Electric	HSEBCAGS176TW01, HSEBYAGS176TW01
	Gas	HSGBACGS116TW01
Capacity - lb (kg)		18 (8.2)
Cylinder Volume - cu. ft. (liters)		7.0 (198)
Width - in (mm)		26.875 (683)
Depth - in (mm)		28 (711)
Height - in (mm)		78.19 (1986)
Motor Size - HP (kw)		0.33 (0.25)
Available Heat Sources		Electric or Gas
Available Heating Element (Electric W)		4750 @ 208V 5350 @ 240V
Gas Inlet Connection - in (mm)		3/8 (9.5)
Gas Consumption - BTU/Hr		25,000
Exhaust Outlet Diameter - in (mm)		4 (102)
Exhaust Airflow - cfm (liters/sec)		220 (105)
Available Cycles*		High, Medium, Low, Delicates
Cycle Indicator Lights		Yes
Cylinder Finish		Galvanized
Available Colors		White
Door Type		Solid
US Electrical Requirements - (Voltage/Hz/Ph)		Electric: 208-240/60/1 - 30 Amp Gas: 120/60/1 - 15 Amp
Canada Electrical Requirements - Single Supply Cord (Voltage/Hz/Ph)		Electric: 208-240/60/1 - 60 Amp Gas: 120/60/1 - 20 Amp
Shipping Dimensions - in (mm)	Width	29 (737)
	Depth	32 3/4 (832)
	Height	80 (2032)
Net Weight - lb (kg)		Elec/Gas 265/275 (120/125)
Shipping Weight - lb (kg)		Elec/Gas 280/290 (127/132)
Available Agency Approvals		Elec: C <sup>UL</sup> US, - Gas: C <sup>CSA</sup> US

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.

©Copyright 2022 Alliance Laundry Systems LLC

\* Information shown applies to highest end control available.

Note: Not all options are available for all models.  
Twelfth digit in model number indicates US or Canadian unit. C=Canada & T=US.

Refer to the price list for the available models and options.

Lower unit is ADA Compliant.